

# Russellstoll®

## Heavy Service Ever-Lok® – Receptacle Mounting Options

### Receptacle Mounting Options

Progressive Assembly

Mounting Style		To Order Use:	Current Rating 30 Amp	60 Amp	100 Amp
Standard Series <b>HSA</b> 		Receptacle +	Basic Receptacle* +	Basic Receptacle* +	Basic Receptacle* +
		Vertical or Square Mount Box +	JB3 1" Std. Conduit Size +	JB6 1½" Std. Conduit Size +	JB10 2" Std. Conduit Size +
		Angle Adapter	JAA3 (20°) or JAA3-45 (45°)	JAA6-AB6 (20°) or JAA6-45 (45°)	JAA10 (20°) or JAA10-45 (45°)
Series <b>HSR</b> Straight 		Receptacle +	Basic Receptacle* +	Basic Receptacle* +	Basic Receptacle* +
		Vertical Mount Box +	JB3 1" Std. Conduit Size +	JB6 1½" Std. Conduit Size +	JB10 2" Std. Conduit Size +
		Straight Adapter	JRA3	JRA6-AB6	JRA10
Series <b>HSB</b> 		Receptacle +	Basic Receptacle* +	Basic Receptacle* +	Basic Receptacle* +
		30° Angle Adapter	JAAB3	JAAB6	JAAB10
Series <b>HSE</b> 		Receptacle +	Basic Receptacle* +	Basic Receptacle* +	N/A
		Angle Enclosure	JE3 1" Std. Conduit Size	JE6 1½" Std. Conduit Size	
Series <b>HSH</b> Horizontal 		Receptacle +	Basic Receptacle* +		N/A
		Horizontal Mount Box +	JB3 1" Std. Conduit Size +	N/A	N/A
		Angle Adapter	JHA3 (20°)		

\* Select appropriate receptacle by rating, configuration and voltage on Page H108.

**Ordering:** Order individual pairs or use series letters followed by receptacle I.D. (ref. HSA series number). Example: HSB8414.  
(For HSA use receptacle catalog numbers only.)