

Russellstoll®

Delayed Action Receptacles (EFS and DA)

Accessories

Cable Bushings

For Explosion Proof Plugs & Connectors

To order non-standard bushing, add cable bushing number to end of catalog number. This is furnished at no additional cost at time of order. For 60 A devices, see J-line 60A chart on page H41.

Hole Diameter for Cable	Cat. No.	Hole Diameter for Cable	20A Cat. No.
.312"	SG05	.563"	SG25
.375"	SG1	.594"	SG2B
.438"	SG15	.625"	SG3
.500"	SG2	.687"	SG3A
.531"	SG2A	.750"	SG4



Material – Oil Resistant Neoprene.

Note: Cable outside diameter should be at or slightly less than bushing I.D. Bushings can compress approx. 10% at installation.

To Order add suffix as examples: 4466/SG3

H

Russellstoll®

Flap Cover Assembly

For 20 Amp Delayed Action Circuit Receptacles

Part No.	Finish	Used on Cat. No.
F19054C	Chrome Plated	4445
F19054D	Natural Finish	4464

Combination Gland Nut and Cable Clamp

For 20 Amp Delayed Action Circuit Plugs

Provides extra clamping protection in hard service applications.

Part No.	Used on Cat. No.
F24853C	4466
F24853D	4467



Material – Cast aluminum alloy, natural finish