

Accessory 14 - Auxiliary Contacts (to indicate status of main contacts)

ACCESSORY (WITH SUFFIX LETTER)	QUANTITY OF FORM C SPDT CONTACTS	AUXILIARY CONTACT RATINGS
14H	1	10 amps at 277 VAC
14HA	2	10 amps at 277 VAC

Accessory 47, 48, 49 - Solid-State Control Modules

These Control Modules provide control flexibility. They mount directly onto the base, either at the bottom (up to 6-pole unit) or on the right side (over 6-pole unit).

ACCESSORY	CONTROL VOLTAGE	AC POWER REQUIREMENTS	DC POWER REQUIREMENTS
Solid State Control Module for 2-wire control; specify letter suffix for control voltage			
47P	12 VAC & DC	0.60 VA	0.32 watt
47M	24 VAC & DC	0.85 VA	0.36 watt
47L	120 VAC	1.90 VA	-
47N	240 to 277 VAC	4.00 VA	-
Solid-state control module for 3 wire control; specify letter suffix for control voltage			
48P	12 VAC & DC	0.34 VA	0.36 watt
48M	24 VAC & DC	0.34 VA	0.38 watt
48L	120 VAC	1.60 VA	-
48N	240 to 277 VAC	2.50 VA	-
Solid-state control module for stop/start control (Form 3); specify letter suffix for control voltage			
49N	12 VAC & DC	0.68 VA	0.70 watt
49L	24 VAC & DC	0.70 VA	0.72 watt
49K	120 VAC	3.70 VA	-
49M	240 to 277 VAC	6.00 VA	-