

Russellstoll®

Hazardous Duty Plugs, Receptacles and Interlocks

Explosion-Proof Waterproof Circuit Breaker Interlocked Receptacle

Available in 30, 60 and 100 AMP sizes, all polarizations. Division 1, Class I & II

Heavy duty XP cast aluminum housing, electrostatic epoxy coat finish.

Standard, high AIC and NA (switched only) breakers available.

Threaded access (cover not shown) with "O" ring for XP and waterproof integrity.

Gated dead-front safety.

Drain Plug.

Factory sealed receptacle interior. Accepts standard XP rated MaxGard plugs.

UL and CSA listed for hazardous locations.

Class I, Division 1, Groups B, C and D
Class II, Division 1, Groups F and G
UL File E10919

NEMA 7, 8, 9

CSA

D.O.T. shipboard used above deck "green water"

NEMA 4X

USCG approved.

MaxGard DBRE and DSRE series interlocks are the only devices certified both explosion proof and waterproof, along with optional control contacts, fully UL listed.

Explosion-Proof Waterproof Non-Interlocked Receptacle

Available in 30A 480VAC max., all polarizations.

Heavy duty XP cast aluminum housing, electrostatic epoxy coat finish.

Threaded access with (cover not shown) "O" ring for XP and waterproof integrity.

Gated dead-front for safety.

All standard polarizations available to 480VAC.

Factory sealed receptacle interior. Accepts standard XP rated MaxGard plugs.

UL and CSA listed for hazardous locations.

Class I, Division 1, C and D

Class II, Division 1, Groups F and G

UL File E10919

NEMA 7, 8, 9

CSA

D.O.T. shipboard used above deck "green water"

NEMA 4X

USCG approved.

- **Factory Sealed Interior (no filled conduits).**
- **Easy low cost installation.**



Russellstoll®

H