

Russellstoll®

Mechanically Interlocked Receptacles – Ordering Information

Mechanically Interlocked Receptacle with Switch

Rating:

20 Amp/600VAC

30 Amp/250VAC



Poles/Wires	Aluminum** Receptacle w/Box	FS/FD Plug	Brass Receptacle w/Box	FS/FD Plug	DuraGard Plug	Bushing I.D.
2P3W	F20493C	3750	1593LP	3750B	9P33UØ	5/8"
3P4W	F20493A**	3760	1594LP	3760B	9P34UØ	3/4"

**Flap cover brass version Suffix -B.

Mechanically Interlocked Receptacle with Circuit Breaker

Rating:

20 Amp/250VAC

30 Amp/250VAC



Poles/ Wires	Trip Rating	Aluminum Receptacle w/Box	FS/FD Plug	DuraGard Plug	Bushing I.D.
2P3W	20A	F33048B	3750	9P33UØ	5/8"
	30A	F33048C	3760		
3P4W	20A	F33054B	3760	9P34UØ	3/4"
	30A	F33054C	3760		
3P4W	50A	C1479AH	3760	9P34UØ*	7/8"

Note: For Panel Mounting or Cover Assemblies only, please contact factory.

* Consult Technical Services for all 50A Trip applications (30a device, 50A trip) See also DuraGard Interlocks. For brass versions, contact Technical Services.

H

Russellstoll®