Russellstoll*

UniGard™ Pin & Sleeve IEC Connector





E2630 E47956



F205590





Beverage Plants



Construction Sites



Food Processing



Marine and Shipboard



Pulp & Paper Mills



Chemical Plants

Safety, Performance and Durability... In A Snap!

Extensive Product Family

- Safe and reliable, portable electrical connections.
- Wide variety of Plugs, Connectors, Receptacles, Inlets and Mounting Boxes.
- Watertight (IP67) and Splashproof (IP44) versions available.
- 20, 30, 60 and 100 Amp ratings for small, medium or large current loads.
- CULus Listed for North American ratings.
- UL classified to IEC309-1 and IEC309-2 for North American and International ratings.
- Complete interchangeability with all manufacturers' IEC309-1 and IEC309-2 devices.
- Meets IEC309 global configurations for safety in industrial applications.

Watertight

- Watertight design and construction meet stringent IP67 internal protection standards.
- Rugged thermoplastic housings resist impact or abuse and provide excellent corrosion resistance.
- Unique Thomas & Betts strain relief grip and sealing system assure superior cable retention and watertight conductor termination.
- Ideal for outdoor, wet, marine and washdown applications.
- Unique 75% faster assembly with EZ Clik™ handle locking, and EZ Tite™ cable grip system.

Splashproof

- Suitable for indoor use where splashing liquids and other contaminants may interfere with electrical connections.
- Ideal for most heavy commercial applications and light industrial applications.
- Available in 20 and 30 Amp ratings.



Russellstoll*

UniGard™ Safety, Performance and Durability

EZ Clik™ locking mechanism



The Easy Way -EZ Clik™ locking

and connectors.

feature on all 20/30A plugs

Self-Aligning Solid Contacts -

- Self-aligning Nickel plated full-round pins and sleeves for maximum cool contact area.
- Sleeve pressure rings ensure constant surface contact force.
- Nickel plating offers maximum corrosion for any use.

Screw Collars Stay Put – Turreted grip allows for easy handling.

75% Faster Cable Builds – EZ TITE™ System

- One-piece cable gland.
- Nylon locking screw prevents loosening.
- EZ hand assembly of cable gland, Grip Tite™ 6-Finger clamp and onion-ring bushing.



Safe Connections Standard -


Ground contacts make first, break last for safe connections even under load.



Russellstoll®

Combination Flap/Screw Cover -

- Integral neoprene gasket for IP67 Watertight protection.
- Standard flap cover for IP44 Splashproof protection.
- Unique flex hinge design.




Fast and Easy Wiring -

- Unique, one-way terminal access.
- Clearly marked terminal connections.

Double Secure Wiring -

• Dual, combination point terminal screws for failsafe connections.





Solid, Safe Voltage Selections -

One-Piece contact carriers with Full-Color IEC standard voltage-phasing Coding ensures correct product application every time.

Standard Interface / World Ready Full International Compliances -

EN60309

UL Classification to IEC309-1 and IEC309-2. CULus Listing: UL1682/1686 and CSA C22.2

CE conforms to EC Low Voltage Directive. North American and Global Voltage



Russellstoll*

Features


No Tools, No Screws Necessary

- EZ Clik™ locking handle saves 75% on assembly time.
- Unique EZ Clik™ assembly feature on 20 and 30 Amp plugs and connectors makes installation and inspection fast and reliable.
- Captured gaskets in handles seal out water, chemicals and dust.



Easy Action Single-Wiring Point Access Saves Time Wiring

- All terminal screws face in same direction allowing installer to make safe and secure conductor terminations in 30% less time than other devices.
- Rugged, corrosion free thermoplastic housings are color-coded for safe and reliable connections to all other mating type/polarizations, with raised ground terminal standard.



Simple Cable Clamping

- Threaded EZ Tite[™] cable gland on 20 and 30 Amp devices makes assembly fast and easy.
- One-piece lock screw verifies clamp locking hold, with no external metal contact possible. (20 and 30 Amp devices)



Unique Fast Assembly

- One-piece EZ Tite™ cable gland with locking screw loads to cable followed by Grip Tite™ 6-Finger cable clamp/grip piece.
- Watertight onion ring bushing fits a wide variety of outside diameters.



Watertight and Grip Tite™ Safety

- Grip Tite™ flexible 6-finger clamp teeth holds well beyond all agency test pullout forces.
- No internal clamps required.
- Available in all amperages.



The Performance Connection

- Watertight spring-loaded covers with high-strength flex-hinge screw covers on IP67 devices.
- Flap covers on IP44 splashproof styles.
- Safety, performance and durability for all IEC309 applications worldwide.

