

# ASCO 920 Remote Control Switch Ordering Information

To order an ASCO 920 Remote Control Switch, complete the following catalog number:

920	+ 3	+ 225		+ 7		+ 1	+ X	+ C
PRODUCT	POLES	AMPS		VOLTAGE2 CODE		SUB PANEL	OPTIONS	ENCLOSURE
920	2	Continuous Ampere Rating		3	110 to 120 V	0 = No <sup>3</sup> Sub Panel  1 = Sub Panel	Leave blank if no options. "X" indicates options, list separately. See below.	Leave blank if open type, or use C for NEMA Type 1 or specify other type required.
				6	208 to 240 V			
	3	AC/DC <sup>1</sup>	AC	7	265 to 277 V			
				9	440 to 480 V			
		30	100	X	Other Voltages up to 480			
		60	150					
		75	200					
		225						

1. For DC service, maximum current rating is 75 amps or switch rating, whichever is less, with maximum voltage rating of 125 volts when connected 1 pole to load and 250 volts when connected 2 poles to load.
2. All at 50 or 60 Hz. For voltages other than those listed, and for DC applications, contact your nearest ASCO source.
3. Specified only when ASCO 920 is to be mounted within panelboard. A sub-panel is required when mounting in NEMA type enclosures.

Catalog Number example above, 920322571XC, Accy 48 is for an ASCO 920, standard 3-pole, 225 amp switch with a control coil voltage of 227 volts 60 Hz, with an Accessory 48 and a sub panel, in a NEMA Type 1 enclosure.